







CATALOG 2026

LED strip lighting & accessories catalogue — 83 products

CONTENTS

	LED Strip	21 items
	Neon Flex	21 items
	Power Supply	9 items
	Controller	15 items
	Accessorie	17 items



LED Strip

LED Strip · 21 items

ARUM



COB Strip Light RGBW (3000K) 24V

RGBW

COB RGBW LED strip combining RGB and warm white 3000K in one strip — flexible for any mood

Voltage	24V DC	LED Chip	COB 784LED/m
Lumens	920 Lumen/m	Power	20W/m
Length	10 m/roll	Cut Interval	32mm
Beam Angle	180°	Dimension	12×1.6 mm
Color	RGBW (RGB + 3000K Warm White)	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



COB Strip Light RGB 24V

RGB

COB RGB LED strip with 16 million color choices, 840 LED/m — endless mood control

Voltage	24V DC	LED Chip	COB 840LED/m
Lumens	726 Lumen/m	Power	15W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	10×1.6 mm
Color	RGB (16 màu)	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION




COB LED Strip RGB SPI Magic Color 24V


RGB SPI

SPI Addressable COB strip — every pixel controlled independently, 20 pixels/m, for clubs and parties

Voltage	24V DC	LED Chip	COB 720LED/m
IC Chipset	WS2812 (SPI Addressable)	Lumens	1923 Lumen/m
Power	23W/m	Length	10 m/roll
Cut Interval	50mm	Beam Angle	180°
Dimension	12×1.6 mm	Color	RGB SPI Addressable (16.7 màu)
IP Rating	IP20 (Indoor)	Warranty	2 years

CROSS-SECTION





Side View COB Strip Light 24V

Side View

Side-emitting COB LED strip — bends freely, no visible glare from above, ideal for signage and trim

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	650 Lumen/m	Power	10W/m
Length	10 m/roll	Cut Interval	33mm
Beam Angle	120°	Dimension	8×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip Ultra Cool White Jewelry Display

Jewelry

Ultra Cool White COB LED — engineered to maximize sparkle on diamonds and gems

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	1140 Lumen/m	Power	12W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	8×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

8500K-8800K (Ultra Cool White)

10000K (Diamond White)




COB LED Strip IP68 Silicone Extrusion 24V

IP68

IP68 fully submersible COB LED — perfect for swimming pools and spa applications

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	570 Lumen/m	Power	6W/m
Length	10 m/roll	Beam Angle	180°
Dimension	10×5.5 mm	CRI	Ra≥80
IP Rating	IP68 (Submersible)	Max Depth	ไม่เกิน 1 m
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)




COB LED Strip 480C IP67 24V

กันน้ำ

IP67 waterproof COB LED — for indoor and outdoor, smooth light even in wet areas

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	855 Lumen/m	Power	9W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	10×1.6 mm
CRI	Ra≥90	IP Rating	IP67 (Waterproof)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 1280C 24V

Pro

Maximum density COB LED 1280LED/m — brightest output at 1650 Lumen/m

Voltage	24V DC	LED Chip	COB 1280LED/m
Lumens	1650 Lumen/m	Power	15W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	12×1.4 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 480C 5mm 24V

5mm

Tiny 5mm COB LED — hides anywhere, perfect for minimalist designs

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	665 Lumen/m	Power	7W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	5×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 528C 24V

แสงสูง

Sharp bright COB LED — ideal for work areas and detailed visual tasks

Voltage	24V DC	LED Chip	COB 528LED/m
Lumens	1260 Lumen/m	Power	14W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	10×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 480C 24V

ไฟห้องนอน

Energy-efficient COB LED — soft non-glare light easy on the eyes

Voltage	24V DC	LED Chip	COB 480LED/m
Lumens	570 Lumen/m	Power	6W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	8×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 320C 12V

Best Value

Entry-level 12V COB strip at a budget price — genuine COB quality, perfect for DIY beginners

Voltage	12V DC	LED Chip	COB 320LED/m
Lumens	960 Lumen/m	Power	12W/m
Length	5 m/roll	Cut Interval	25mm
Beam Angle	180°	Dimension	8×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)



COB LED Strip 320C 24V

ใหม่

Soft COB LED — gentle non-glare light creating a warm relaxing atmosphere

Voltage	24V DC	LED Chip	COB 320LED/m
Lumens	960 Lumen/m	Power	12W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	8×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)




COB LED Strip Dual Color 24V

ใหม่

COB LED strip adjustable from 2700K to 6500K in one strip — shift room mood anytime

Voltage	24V DC	Power	15W/m
Brightness	1650 Lumen/m	Color Temperature	CCT 2700K-6500K
LED Chip	840 LED/m	Length	10 m/roll
Cut Interval	50mm	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



COB LED Strip Running Water Series 24V

Running Water

Running water effect COB LED strip — continuous flowing light, eye-catching, adds movement to any design

Voltage	24V DC	LED Chip	COB 720LED/m
Lumens	1923 Lumen/m	Power	23W/m
Length	10 m/roll	Cut Interval	50mm
Beam Angle	180°	Dimension	12×1.6 mm
CRI	Ra≥90	IP Rating	IP20 (Indoor)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Cool White)




S-Type Zigzag LED Strip 24V

S-Type

S-Type LED strip that bends freely in zigzag curves — ideal for curved paths and non-straight runs

Voltage	24V DC	LED Chip	SMD2835 120LED/m
Lumens	800 Lumen/m	Power	8W/m
Length	10 m/roll	Cut Interval	50mm
Dimension	6×1.6 mm	Light Output	3000K / 4000K / 6000K
IP Rating	IP20 (Indoor)	Warranty	2 years

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Cool White)



Lumabar LED Light Bar 24V

Lightbox

LED light bars for lightboxes — even illumination for backlit stone, onyx, and backlit displays

Voltage	24V DC	LED Count	12 LEDs/bar
Brightness	1,320 lm/bar	Power	12W/bar
Color Temperature	3000K / 6000K	Length	950mm/bar
IP Rating	IP20	Warranty	2 years

CROSS-SECTION



OPTIONS

Warm White 3000K

Cool White 6000K




LED Matrix Panel 24V

Lightbox

LED matrix panels for large lightboxes — even wide-area illumination, cuttable, only 1.4mm thin

Voltage	24V DC	LED Count	120 LEDs/panel
LED Chip	SMD2835	Power	15W/panel
Color Temperature	6000K	CRI	>80 Ra
Panel Size	480 × 240 × 1.4mm	IP Rating	IP20
Warranty	2 years		

CROSS-SECTION





COB LED Strip 220V 432C IP67

220V

220V COB LED strip — direct mains connection, no transformer needed, 50m per roll, IP67 waterproof

Voltage	AC 220-240V	LED Chip	COB 432 LED/m
Power	12 W/m	Length	50 m/roll
Cut Interval	16.6mm	Dimension	10×6 mm
Beam Angle	180°	IP Rating	IP67 (Waterproof & Dustproof)
Warranty	2 years		

OPTIONS

3000K · Full roll 50m

3000K · Per meter

4000K · Full roll 50m

4000K · Per meter

6000K · Full roll 50m

6000K · Per meter



COB LED Strip 48V 480C IP20

Coming soon

48V COB LED strip — new system, 30m per roll, 4× lower voltage drop than 24V, for commercial indoor use


Voltage	48V DC	LED Chip	COB 480 LED/m
Power	10 W/m	Length	30 m/roll
Beam Angle	180°	IP Rating	IP20 (Indoor)
Warranty	2 years		

OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Cool White)



COB IP67/IP68 End Cap & Outlet Cap

10mm

End caps for 10mm COB LED Strip IP67/IP68 — 2 styles to choose from

Compatible With	COB LED Strip IP67 / IP68	Size	10mm
Material	High-grade silicone	Waterproof Rating	IP67 / IP68

OPTIONS

End Cap (sealed)

Outlet Cap (with wire-feed hole)



Neon Flex

Neon Flex · 21 items

ARUM



Neon Flex 0612 (6×12mm) 12V

6×12mm

Compact 6×12mm Neon Flex, side-bend capable, IP65 waterproof — perfect for narrow channels

Voltage	12V DC	LED Chip	COB 60LED/m
Lumens	500 Lumen/m	Power	8W/m
Length	5 m/roll	Cut Interval	25mm
Dimension	6×12 mm	Bending	Side Bend (ดัดแนวข้าง)
IP Rating	IP65 (กันน้ำ)	Warranty	2 years

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)
- 6000K (Daylight)
- Red
- Blue
- Green
- Pink
- Yellow



Neon Flex 0612 (6×12mm) 12V — Full 50m Roll

ยกม้วน

Small 6×12mm Neon Flex by the 50m roll — side-bend, IP65, bulk pricing for contractors

Voltage	12V DC	LED Chip	COB 60LED/m
Lumens	500 Lumen/m	Power	8W/m
Length	50 m/roll	Cut Interval	25mm
Dimension	6×12 mm	Bending	Side Bend (ดัดแนวข้าง)
IP Rating	IP65 (กันน้ำ)	Warranty	2 years

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)
- 6000K (Daylight)
- Red
- Blue
- Green
- Pink
- Yellow



Neon Flex 0816 (8×16mm) 220V

220V

220V Neon Flex with excellent bendability — smooth dotless light, IP65, no transformer needed


Voltage	220V AC	LED Chip	SMD2835 120LED/m
Lumens	216-234 Lumen/m	Power	9W/m
Length	1 m	Cut Interval	1000mm (1 m)
Dimension	8×16 mm	IP Rating	IP65 (กันน้ำ)
Warranty	2 years		

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)
- 6000K (Daylight)
- Red
- Blue
- Green
- Pink
- Yellow




Neon Flex 1010(10×10mm) 24V

IP67

Square 10×10mm Neon Flex — IP67 waterproof, UV-resistant for indoor and outdoor use

Voltage	24V DC	LED Chip	288LED/m
Lumens	250-300 Lumen/m	Power	5W/m
Length	10 m	Cut Interval	50mm
Dimension	10×10 mm (สี่เหลี่ยม)	Bending	Side Bend (ัดแนวข้าง)
IP Rating	IP67 (UV & rain resistant)	Warranty	2 years

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)




Neon Flex 1616(16×16mm) 24V

IP67

Mid-size 16×16mm Neon Flex — IP67 waterproof, easy to bend, prominent light for displays and signage

Voltage	24V DC	LED Chip	SMD2835 120LED/m
Lumens	864 Lumen/m	Power	14W/m
Length	10 m	Cut Interval	50mm
Dimension	16×16 mm	Bending	Side Bend (ัดแนวข้าง)
IP Rating	IP67 (Waterproof)	Warranty	2 years

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)
- 6000K (Cool White)
- Red
- Green
- Blue
- Yellow
- Pink

ARUM

Neon Flex Glare-Free 1616 (16×16mm) 24V


Coming soon

Glare-Free 24V Neon Flex 16×16mm — soft comfortable light, ideal for cove lighting and premium spaces

Voltage	24V DC	Dimension	16×16 mm
Length	10 m/roll	IP Rating	IP67 (Waterproof)
Special Features	Glare-Free Diffuser	Warranty	2 years

OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)
- 6000K (Cool White)





Neon Flex RGB 1616 (16×16mm) 24V

RGB

RGB Neon Flex 16×16mm with 16 million colors, IP67 waterproof — bends well, ideal for displays and graphics

Voltage	24V DC	LED Chip	SMD2835 96LED/m
Lumens	864 Lumen/m	Power	14W/m
Length	10 m	Cut Interval	50mm
Dimension	16×16 mm	Color	RGB (16 ล้านสี)
Bending	Side Bend (ด้านข้าง)	IP Rating	IP67 (Waterproof)
Warranty	2 years		

CROSS-SECTION




Black Neon Flex 1220 (12×20mm) 24V

ใหม่

Stealth matte-black Neon Flex 12×20mm — invisible in modern dark interiors, IP67 waterproof

Voltage	24V DC	LED Chip	SMD2835 120LED/m
Lumens	700-840 Lumen/m	Power	14W/m
Length	10 m	Cut Interval	50mm
Dimension	12×20 mm	Bending	Side Bend (ด้านข้าง)
IP Rating	IP67 (Waterproof)	Warranty	2 years

CROSS-SECTION



OPTIONS

- 3000K (Warm White)
- 4000K (Natural White)



Neon Flex 1616 (16×16mm) 220V

220V

220V Neon Flex — direct mains power, no transformer needed, 16×16mm, IP67 waterproof

Voltage	220V AC	LED Chip	120LED/m
Lumens	840 Lumen/m	Power	12W/m
Length	ขายเป็นม	Cut Interval	100mm
Dimension	16×16 mm	Bending	3D Bend (ตัดได้ทุกทิศทาง)
IP Rating	IP67 (Waterproof)	Warranty	2 years

CROSS-SECTION



Neon Flex 360° 24V

360°

360° all-around illumination Neon Flex — round 20mm profile, 3D bendable, IP67 waterproof

Voltage	24V DC	LED Chip	SMD2835
Lumens	840 Lumen/m	Power	14W/m
Length	10 m/roll	Cut Interval	50mm
Dimension	Ø20 mm (ทรงกลม)	Bending	3D Bend (ตัดได้ทุกทิศทาง)
Beam Angle	360° (รอบๆ)	IP Rating	IP67 (Waterproof)
Warranty	2 years		

CROSS-SECTION



OPTIONS

3000K (Warm White)

4000K (Natural White)

6000K (Daylight)




Corner Neon Flex 24V

Top Bend

Top-bend Neon Flex for vertical corners — sharp angled light lines, seamless 90° turns, IP65

Voltage	24V DC	LED Chip	168LED/m
Lumens	760 Lumen/m	Power	10W/m
Length	10 m/roll	Cut Interval	35.7mm
Dimension	8.9×18.9 mm	Bending	Top Bend (ตัดแนวตั้ง)
IP Rating	IP44	Warranty	2 years

CROSS-SECTION



OPTIONS

2700K (Extra Warm White)

3500K (Warm White)



Neon Flex Mounting Track 1010

1010

Stainless steel snake-style mounting track — bends to follow any Neon Flex 10×10mm shape

Model	1010	Neon Flex Compatibility	ขนาด 10x10mm
Material	สแตนเลส	Color	สีสแตนเลส
Sold by	ต่อม	Full Roll	100 m



Neon Flex Mounting Track 1616

1616

Stainless steel snake-style mounting track — bends to follow any Neon Flex 16×16mm shape

Model	1616	Neon Flex Compatibility	ขนาด 16x16mm
Material	สแตนเลส	Color	สีสแตนเลส
Sold by	ต่อม	Full Roll	100 m




Neon Flex Mounting Track 0816

0816

White PVC clip-in mounting track for Neon Flex 8×16mm — secure hold, won't slip

Model	0816	Neon Flex Compatibility	ขนาด 08x16mm
Material	PVC	Color	ขาวขุ่น (Milky White)
Channel Width	10×10mm	Length	1 m
Installation	ใช้สกรูยึด		



Neon Flex End Cap 1010


1010

End caps for 10×10mm Neon Flex — 2 styles to choose from

Model	1010 (10×10mm)	Material	High-grade silicone
Color	Clear/White	Neon Flex Compatibility	ขนาด 10x10mm

OPTIONS

- Outlet Cap (with wire-feed hole)
- End Cap (sealed)



Neon Flex End Cap 1616

1616

End caps for 16×16mm Neon Flex — 3 styles to choose from

Model	1616 (16×16mm)	Material	High-grade silicone
Color	Clear/White	Neon Flex Compatibility	ขนาด 16x16mm

OPTIONS

- Outlet Cap (with wire-feed hole)
- End Cap (sealed)
- Side Outlet Cap (side wire-feed)



Neon Flex Endcap — Black 1220


1220 Black

Black endcaps for Black Neon Flex 12×20mm — 2 types, waterproof, dustproof finish

Model	1220 (12×20mm)	Material	High-grade silicone
Color	ดำ	Neon Flex Compatibility	Black Neon Flex ขนาด 12x20mm

OPTIONS

- Outlet Cap (with wire-feed hole)
- End Cap (sealed)



Neon Flex Endcap — Corner


Corner

Endcaps for Corner Neon Flex 8.9×18.9mm — 2 types, waterproof, dustproof

Model	Corner Neon Flex (8.9×18.9mm)	Material	High-grade silicone
Color	ขาว	Neon Flex Compatibility	Corner Neon Flex ขนาด 8.9x18.9mm

OPTIONS

- Outlet Cap (with wire-feed hole)
- End Cap (sealed)



Neon Flex Clip Lock

Clip Lock

Mounting clips for Neon Flex — multiple sizes to fit each Neon Flex variant

Material	พลาสติกคุณภาพสูง	Color	Clear/White
Neon Flex Compatibility	หลายขนาด (เลือกตาม variation)		

OPTIONS

- Size 0612 (100 pcs/pack)
- Size 0816 (100 pcs/pack)
- Size 1010 (50 pcs/pack)
- Size 1616 (50 pcs/pack)
- Size 1220 (50 pcs/pack)
- Corner Neon Flex (50 pcs/pack)



Neon Flex Power Plug — 0816 220V

0816

Mains power plug connector for Neon Flex 0816 220V — plug directly into wall socket

Neon Flex Compatibility	0816 (8×16mm) 220V	Voltage	220V AC
Material	พลาสติกคุณภาพสูง		



Aluminum Profile — Neon Flex 1616

1616

Aluminum mounting profile for Neon Flex 16×16mm — clean installation, heat dissipation, longer life

Length	1 m	Material	Aluminum Alloy
Color	Silver Anodized	Neon Flex Compatibility	ขนาด 16x16mm
Total	รางอลูมิเนียม + คลิปยึด		

CROSS-SECTION



⚡ Power Supply

Power Supply · 9 items

ARUM



Arum Hyper Switching PSU 24V

Premium

High-quality 24V PSU with double-sided circuit board — stable power, full protection suite, 3-year warranty

Input Voltage	AC 100-277V	Output Voltage	24V DC
Power	100W / 200W / 300W / 400W	PCB	Double-sided Fiberglass Board
IP Rating	IP20 (Indoor)	Warranty	3 ปี

OPTIONS

100W 200W 300W 400W



ARUM Core Power Supply 24V

คุ้มค่าที่สุด

Value 24V power supply — compact, ideal for general installations under moderate load. 1-year warranty

Input Voltage	AC 100-240V	Output Voltage	24V DC
Power	60W / 100W / 200W / 300W / 400W	IP Rating	IP20 (Indoor)
Warranty	1 year		

OPTIONS

60W 100W 200W 300W 400W



Arum Core Power Supply 12V

คุ้มค่าที่สุด

Value-for-money compact 12V PSU for general indoor LED installations — 1-year warranty

Input Voltage	AC 100-240V	Output Voltage	12V DC
Power	60W / 100W / 200W / 300W / 400W	IP Rating	IP20 (Indoor)
Warranty	1 year		

OPTIONS

60W 100W 200W 300W 400W



Arum XT Power Supply 24V

มีหน้าจอ

24V PSU with real-time Volt and Watt display — monitor your LED load live, 2-year warranty

Input Voltage	AC 100-240V	Output Voltage	DC 24V
Power	60W / 100W / 200W / 300W / 400W	Display	แสดงค่า Volt และ Watt แบบเรียลไทม์
IP Rating	IP20 (Indoor)	Warranty	2 years

OPTIONS

60W 100W 200W 300W 400W



Arum Waterproof Power Supply 24V (IP67)

Last Stock

24V waterproof IP67 PSU for outdoor use — sun and rain resistant. 2-year warranty

Input Voltage	AC 100-240V	Output Voltage	24V DC
Power	60W / 100W / 200W / 300W / 400W	IP Rating	IP67 (Waterproof & Dustproof)
Warranty	2 years		

OPTIONS

60W 100W 200W 300W 400W



Arum Waterproof Power Supply 12V

Last Stock

IP67 waterproof 12V PSU for outdoor LED — rain and sun resistant, 2-year warranty

Input Voltage	AC 100-240V	Output Voltage	12V DC
Power	60W / 100W / 150W / 200W / 300W / 400W	IP Rating	IP67 (Waterproof & Dustproof)
Warranty	2 years		

OPTIONS

- 60W
- 100W
- 150W
- 200W
- 300W
- 400W



Arum RainX Power Supply 24V (IP67)

IP67 กันน้ำ

Premium 24V IP67 RainX PSU — sun and rain resistant, ideal for outdoor installs

Input Voltage	AC 100-240V	Output Voltage	24V DC
Power	100W / 200W / 300W / 400W	IP Rating	IP67 (Waterproof & Dustproof)
Warranty	2 years		

OPTIONS

- 60W
- 100W
- 200W
- 300W
- 400W



Arum RainX Power Supply 12V

IP67 กันน้ำ

Budget 12V IP67 waterproof PSU — weather-resistant outdoor power for small sign and décor projects

Input Voltage	AC 100-240V	Output Voltage	12V DC
Power	100W / 200W / 300W / 400W	IP Rating	IP67 (Waterproof & Dustproof)
Warranty	2 years		

OPTIONS

- 100W
- 200W
- 300W
- 400W



Arum Switching PSU 48V

48V

48V switching PSU for large commercial LED projects — powers 48V strips up to 25m per circuit

Input Voltage	AC 100-240V	Output Voltage	48V DC
Power	200W / 400W	Efficiency	≥ 90%
IP Rating	IP20 (Indoor)	Brand	Arum
Warranty	2 years		

OPTIONS

- 200W
- 400W



Controller

Controller · 15 items

ARUM




Stair Controller

ยอดนิยม

Stair light controller — runs LEDs in sequence step-by-step, supports up to 30 steps

Voltage	12-24V DC	Max Steps	30 steps
Sensor	PIR Motion Sensor x2 (บน-ล่าง)	Modes	วิ่งขึ้น / วิ่งลง / สว่างพร้อมกัน
Timer	ปรับความเร็ว และเวลาดับได้		

CROSS-SECTION



Remote Driver Set — Single Color

Complete remote + driver set for single-color LED strips — up to 288W, 0-100% dimming

Voltage	24V DC	Max Power	288W
Light Type	Single Color (สีเดียว)	Control	RF Remote 2.4GHz
Functions	เปิด/ปิด, หรี่แสง, ตั้งเวลา		

CROSS-SECTION



Remote Driver Set — Dual Color (CCT)

Complete remote + driver set for Dual Color / CCT LED strips — 288W, warm-to-cool adjustment

Voltage	24V DC	Max Power	288W
Light Type	Dual Color / CCT	Control	RF Remote 2.4GHz
Functions	เปิด/ปิด, หรี่แสง, ปรับอุณหภูมิสี		

CROSS-SECTION






Remote Driver Set — RGB / RGBW

Complete remote + driver set for RGB / RGBW LED strips — 288W, 16 million colors

Voltage	24V DC	Max Power	288W
Light Type	RGB / RGBW	Control	RF Remote 2.4GHz
Functions	เปลี่ยนสี, หรี่แสง, โหมดเอฟเฟกต์		

CROSS-SECTION




Remote Driver Set — RGB SPI (Magic Color)

Complete remote + driver set for SPI Addressable RGB LED — 40 running light effects included

Voltage	5-24V DC	Max Current	8A Max
Output Signal	SPI Signal (DATA + CLK)	Light Type	RGB SPI / RGBW SPI (Addressable)
Supported ICs	WS2812B, SK6812, SK6813, WS2811, TM1708, UCS5603 และอื่นๆ	Control	RF Remote 2.4GHz 28 ๒๒
Effects	40 โหมด (horse-race, chase, flow, trail, gradual change)	Operating Temperature	-30°C ~ +55°C

CROSS-SECTION




App Controller — All LED Types

Smart

Smartphone-controlled LED driver for all types: Single / Dual / RGB / RGBW

Voltage	24V DC	Max Power	288W
LED Compatibility	Single / Dual / RGB / RGBW	Connection	Bluetooth / WiFi
App	iOS / Android		

CROSS-SECTION



OPTIONS

- Bluetooth
- WiFi + Bluetooth




Controller SP656E — Single Color Running LED

SP656E

Single-color running / addressable LED controller — Xiaomi app compatible, up to 600 ICs

Model	SP656E	Type	SPI Single Color LED Controller
LED Compatibility	LED Running / Addressable LED (Single Color)	Voltage	5-24V DC
IC Compatibility	สูงสุด 600 ICs	Output Signal	SPI
Operating Temperature	-10 ถึง 60°C	Control	ปุ่มกด / แอป Xiaomi Smart Home

CROSS-SECTION




Rocker Switch Mini

Mini

Tiny furniture-embed rocker switch, AC 6A/250V, 20mm mounting hole

Rated For	6A 250V / 10A 125V	Mount Holes	20mm
Pin	SPST (Single Pole) 2-Pin	Contact Resistance	35mΩ max
Insulation Resistance	≥100MΩ ที่ 500VDC	Operating Temperature	-25°C ถึง +85°C
Lifespan	10,000 รอบ		

CROSS-SECTION



OPTIONS

White

Black



Limit Switch (Door Contact)

ติดตู้

Contact switch for automatic cabinet lighting — open door = light on, close door = light off

Voltage	12-24V DC	Type	Contact Switch
Connection	ต่อสาย DC+ ผ่าน		



Motion Sensor (Cabinet)

เซ็นเซอร์

Block/unblock sensor for cabinet lighting — covers sensor = off, uncovers = on, 60W rated

Voltage	12-24V DC	Max Load	60W
Type	Infrared Sensor		



Dimmer Knob

Dimmer

Rotary dimmer knob for adjusting LED brightness — compatible with 12-24V strips

Voltage	12-24V DC	Type	Rotary Dimmer
---------	-----------	------	---------------




Touch Control Panel T1 — Single Color

T1

Wall-mounted touch panel for single-color LED — circle-gesture dimming, 4 scene presets

Input Voltage	12-48V DC	Output Voltage	2x(12-48)V DC
Output Current	2×5A @12-24V, 2×3A @36-48V	Output Power	2x(60-144)W
Size	86×86mm (ขนาดสวิตช์มาตรฐาน)	Operating Temperature	-30°C ถึง +55°C

CROSS-SECTION




Touch Control Panel T2 — Dual Color (CCT)

T2

Wall-mounted touch panel for Dual Color LED — adjust warm to cool, dimming, 4 scene presets

Input Voltage	12-24V DC	LED Compatibility	Dual Color (CCT)
Size	86×86mm (ขนาดสวิตช์มาตรฐาน)		

CROSS-SECTION




Touch Control Panel T3 — RGB

T3

Wall-mounted touch panel for RGB LED — color wheel, effect modes, speed and brightness controls

Input Voltage	12-24V DC	Output Voltage	3x(12-24)V DC
Output Current	3×4A	Output Power	3x(48-96)W
Size	86×86mm (ขนาดสวิตช์มาตรฐาน)	Operating Temperature	-30°C ถึง +55°C

CROSS-SECTION




Touch Control Panel T4 — RGBW

T4

Wall-mounted touch panel for RGBW LED — color wheel plus dedicated White button, 4 scene presets

Input Voltage	12-24V DC	Output Voltage	4x(12-24)V DC
Output Current	4×3A	Output Power	4x(36-72)W
Size	86×86mm (ขนาดสวิตช์มาตรฐาน)	Operating Temperature	-30°C ถึง +55°C

CROSS-SECTION





Accessorie

Accessorie · 17 items

ARUM



COB LED Strip Middle Connector

กลาง

Inline connector for joining two COB LED strips flush together — no soldering, press-lock

Type **ข้อต่อกลาง (Middle Connector)** Usage **ต่อไฟเส้น COB 2 เส้นเข้าด้วยกัน**

Material **พลาสติกใสคุณภาพสูง + หน้าสัมผัสทองแดง**

OPTIONS

- 2-Pin (Single Color 8mm)
- 4-Pin (RGB 10mm)
- 5-Pin (RGBW 12mm)



COB LED Strip Wire Connector

สาย

Wire connector for spanning gaps between COB LED strip sections — no soldering, 15cm wire

Type **ข้อต่อสาย (Wire Connector)** Usage **ต่อไฟเส้น COB ผ่านสายไฟ เว้นระยะได้**

Material **พลาสติกใสคุณภาพสูง + หน้าสัมผัสทองแดง**

OPTIONS

- 2-Pin (Single Color 8mm)
- 4-Pin (RGB 10mm)
- 5-Pin (RGBW 12mm)



COB LED Strip Corner Connector (L-shape)

มุม L

L-shape corner connector for COB LED — clean 90° turns without bending, press-lock

Type **ข้อต่อเข้ามุม L (Corner Connector)** Usage **เข้ามุม 90 องศา**

Material **พลาสติกใสคุณภาพสูง + หน้าสัมผัสทองแดง**

OPTIONS

- 2-Pin (Single Color 8mm)
- 3-Pin (CCT 10mm)
- 4-Pin (RGB 10mm)



Silicone Flex Cover

ขายต่อเมตร

High-quality silicone sleeve for LED strips — diffuses light softly, hides dots, multiple sizes, sold per meter

Material **High-grade silicone** Available Sizes **10×10 / 12×12 / 16×10 / 18×10 / 20×20 / 30×10 / 40×20 / 50×25 mm**

Minimum **1 m** Color **ขาวขุ่น (Milky White)**

OPTIONS

- 10×10mm
- 12×12mm
- 16×10mm
- 18×10mm
- 20×20mm
- 30×10mm
- 40×20mm
- 50×25mm



AWG Wire for LED

ขายต่อเมตร

AWG22 standard wire for LED connections — choose from 2 to 5 pins, sold per meter

Wire Gauge **22 AWG (0.34mm²)** Material **ทองแดงบริสุทธิ์ หุ้มฉนวน PVC**

Available Pins **2-Pin / 2-Pin IP67 / 3-Pin / 4-Pin / 5-Pin** Minimum **1 m**

OPTIONS

- 2-Pin (Single Color)
- 2-Pin IP67 (Waterproof)
- 3-Pin (Dual Color / CCT)
- 4-Pin (RGB)
- 5-Pin (RGBW)



Aluminum Profile Flanged


มีปีก

Flanged aluminum LED channel for surface mount or recessing — smooth diffused light, no visible dots

Type	แบบมีปีก (Flanged)	Length	1 m
Material	Aluminum Alloy	End Cap	Milky Diffuser (กระจายแสง)
In the Set	รางอลู + ฝาปิด + ฝาปิดหัว-ท้าย + คลิปยึด		

OPTIONS

- Recessed 24×9mm
- Recessed YW Style (1 meter)
- Recessed YW Style (2 meters)



Aluminum Profile Slim


ไม่มีปีก

Slim aluminum profile — for flush mounting with hidden edges

Type	แบบไม่มีปีก (Slim)	Length	1 m
Material	Aluminum Alloy	End Cap	Milky Diffuser (กระจายแสง)
In the Set	รางอลู + ฝาปิด + ฝาปิดหัว-ท้าย + คลิปยึด		

OPTIONS

- Slim 8×7.6mm
- UH Style
- U Style (1 meter)
- U Style (2 meters)



Aluminum Profile Corner (V-shape)

เข้ามุม

V-shape 90° corner aluminum LED channel — designed for cabinet corners, wall corners, and ceiling edges

Type	แบบเข้ามุม (Corner)	Angle	90 องศา
Length	1 m	Material	Aluminum Alloy
End Cap	Milky Diffuser (กระจายแสง)	In the Set	รางอลู + ฝาปิด + ฝาปิดหัว-ท้าย + คลิปยึด

OPTIONS

- Small 10×10mm
- Large 16×16mm



LED Molding

LED concealment molding for ceilings — 4 styles to choose from

Length	2 ม/เส้น	Material	โฟม PU เคลือบแข็ง
Color	ขาว (ทาสีทับได้)	Strip Compatibility	LED Strip / Neon Flex ขนาด 8-12mm
Installation	ติดตั้งด้วยกาว / ตะปูยึด		

OPTIONS

- Edge (straight)
- Curve (rounded)
- Recessed (flush)
- Shadow (decorative)



Electrical Wall Box 3×3"

3×3" ABS plastic electrical wall box for concealing LED PSUs, drivers, and controllers

Size	3×3 นิ้ว (มาตรฐาน)	Material	ABS Plastic
Color	ขาว/ครีม	Heat Resistance	สูงถึง 105°C
Standard	มอก.		

OPTIONS

- Single (1 channel)
- Double (2 channels)




Aluminum Profile — Recessed Floor

Flush-mount recessed floor aluminum LED channel — walkable, load-bearing, smooth diffused light

Length	1 m	Material	Aluminum Alloy
Color	Silver Anodized	Installation	ฝังพื้น (Recessed)
Total	รางอลูมิเนียม + ฝาปิด Diffuser		

OPTIONS

- U Style
- YW Style





Aluminum Stair Nosing Profile

Aluminum stair nosing with built-in LED channel — combines step-edge safety and beautiful lighting

Length	1 ม (ตัดได้ตามต้องการ)	Material	Aluminum Alloy 6063
Color	Silver Anodized	Install Position	บนstepsบันได (Stair Nosing)
Total	รางอลูมิเนียม + ฝาปิด Diffuser + ฝาปิดหัว-ท้าย		

CROSS-SECTION



Clear PVC Channel for Submersible Strip LED

Clear PVC channel for embedding IP68 LED strips underwater — pairs with waterproof COB LED Strip

Length	1 ม	Material	PVC ใส (Clear PVC)
IP Rating	เหมาะกับไฟเส้น IP68	Pairs With	COB LED Strip IP68 Silicone
Style	โปร่งใส แสงผ่านได้ดี		

CROSS-SECTION



Aluminum Profile Black

Black anodized aluminum LED channel — premium look for modern and dark-toned interior design

Length	1 ม	Material	Aluminum Alloy
Color	Black Anodized (ดำ)	Total	รางอลูมิเนียม + ฝาปิด Diffuser

OPTIONS

- U Style
- YW Style



Waterproof Sealing Glue

กันน้ำ

Premium waterproof sealant for IP67/IP68 LED strips — seal ends, secure caps, block water and moisture

Type	กาวซิลิโคนน้ำ (Waterproof Sealing Glue)	Usage	ซิลไฟเส้น LED IP67 / IP68
Size	หลอด	Waterproof Rating	รองรับ IP67 / IP68
Features	ยืดหยุ่น ไม่แตกร้าว ทนแดด ทนฝน		



Aluminum Profile Bendable — Single Wing


ตัดโค้ง

Single-wing bendable aluminum LED profile — hand-bendable, ideal for edge mounting, 1.3–2.0cm channel width

Type	ตัดโค้งปีกเดียว	Height	1.3 cm (13mm)
Length	1 ม	Material	Aluminum Alloy
In the Set	ราง + ฝาครอบซิลิโคน		

OPTIONS

- 1.3cm (16cm bend radius)
- 1.5cm (25cm bend radius)
- 2.0cm (30cm bend radius)



Aluminum Profile Bendable — Double Wing

ตัดโค้ง

Double-wing bendable aluminum LED profile — stronger hold on both sides, hand-bendable, 1.3–2.0cm channel width

Type	ตัดโค้งปีกคู่	Height	1.3 cm (13mm)
Length	1 m	Material	Aluminum Alloy
In the Set	ราง + ฟาครอบซิลิโคน		

OPTIONS

1.3cm (15cm bend radius)

1.5cm (22.5cm bend radius)

2.0cm (27cm bend radius)